
Trimless recessed luminaire


Schil


Luno Quadro C50 100x100 9W 830 ze11009221














Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 4 |
| Screw x6 | 8 |
| Screw self-tapping | 4 |
| Washer D5 | 8 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: | 290x290x88 mm |
|---------------|---------------|
| Net weight: | 2.6 kg |
| | |

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 8.6 w Luminaire luminous flux*: 861 lm Light output*: 100 lm/w Colorful temperature*: 3000 K Color rendering index*: Ra >80 Color temperature stability*: MAC 3 cos *: 0.51 PRA: LC 8/180/44 fixC SR SNC2

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com