## Trimless recessed luminaire

# Schil

# Luno Quadro C85 100x100 9W 940 DW ze11006053




220-240 V





IP20 Ra >90


MAC 3











#### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	4
Screw x6	8
Screw self-tapping	4
Washer D5	8

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements:	290x290x123 mm
Net weight:	2.9 kg

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 9.1 w Luminaire luminous flux\*: 686 lm 75.00 lm/w Light output\*: Colorful temperature\*: 4000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.95 PRA: LC 10/150-400/40 bDW SC PRE2

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com