## Trimless recessed luminaire

## Schil

# Twins A25 22W 840 IP44/20 DA ze11009752




220-240 V





IP44 Ra >80


MAC 3











#### Complectation

Body	1
LED module	2
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements:	232x137x70 mm
Net weight:	1.49 kg

Double

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 21.1 w Luminaire luminous flux\*: 1885 lm Light output\*: 89.00 lm/w Colorful temperature\*: 4000 K Color rendering index\*: Ra >80 Color temperature stability\*: MAC 3 cos \*: 0.93 LCA 25W 350-1050mA one4all SC PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com