Trimless recessed luminaire

Schil

Twins A25 22W 930 IP44/20 DA ze11009754




220-240 V





IP44 Ra >90


МАС 3











Complectation

Body	1
LED module	2
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1

$\ \, \hbox{Dimming by TRIAC accessible on request} \\$

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Measurements:	232x13/x/0 mm
Net weight:	1.49 kg

Double

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 21.1 w Luminaire luminous flux*: 1508 lm Light output*: 71 lm/w Colorful temperature*: 3000 K Color rendering index*: Ra >90 Color temperature stability*: MAC 3 cos *: 0.93 LCA 25W 350-1050mA one4all SC PRA:

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com