## Trimless recessed luminaire



# Twins R25 16W 930 IP44/20 ze11009429




220-240 V





IP44 Ra >90


MAC 3











#### Complectation

Body	1
LED module	2
Conrol gear	2
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1
Screw x6 Screw self-tapping Washer D5	4

#### $\ \, \hbox{Dimming by TRIAC accessible on request} \\$

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements:	300x167x70 mm
Net weight:	1.77kg

Double

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 15.6 w Luminaire luminous flux\*: 1121 lm Light output\*: 72.00 lm/w Colorful temperature\*: 3000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.4 PRA: Mean Well APC-8-250

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com