Trimless recessed luminaire



Twins R25 16W 930 IP44/20 DA ze11009734




220-240 V





IP44 Ra >90


MAC 3











Complectation

| Body | 1 |
|--------------------|---|
| LED module | 2 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |
| Suction Cup | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: | 300x167x70 mm |
|---------------|---------------|
| Net weight: | 1.81 kg |
| | |

Double

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 15 w Luminaire luminous flux*: 1121 lm Light output*: 75.00 lm/w Colorful temperature*: 3000 K Color rendering index*: Ra >90 Color temperature stability*: MAC 3 cos *: 0.97 PRA: LCA 17W 250-700mA one4all SC PRE

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com