## Trimless recessed luminaire



# Triple R25 33W 930 IP44/20 DW ze11009829




220-240 V





IP44 Ra >90


MAC 3











### Complectation

Body	1
LED module	3
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements:	432x167x70 mm
Net weight:	2.46 kg

Triple

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 31.3 w Luminaire luminous flux\*: 2301 lm Light output\*: 74.00 lm/w Colorful temperature\*: 3000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.95 PRA: LC 45/500-1400/50 bDW SC PRE2

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com