

Trimless recessed luminaire




MAC 3

Triple S05 33W 940









220-240 V


IP20

EHE



Ra >90





328x137x50 mm

1.67 kg

4000 K

Mean Well APC-12-350

Complectation

| Body | 1 |
|--------------------|---|
| LED module | 3 |
| Conrol gear | 3 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |
| Suction Cup | 1 |
| | |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Colorful temperature*:

Measurements:

Net weight:

| Triple | |
|---------------------------|------------|
| Body: | Gypsum |
| Illuminant: | LED |
| | |
| Electrical safety class: | II |
| Degree of protection: | IP20 |
| Rated power: | 33.6 w |
| Luminaire luminous flux*: | 2703 lm |
| Light output*: | 80.00 lm/w |

Color rendering index*: Ra >90 MAC 3 Color temperature stability*: cos *: 0.5

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $^{**}-$ the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com

PRA: