
## Trimless recessed luminaire




MAC 3

# Triple S05 33W 830 DW









220-240 V


IP20

EHE



Ra >80





328x137x50 mm

1.57 kg

93 lm/w

3000 K

LC 45/500-1400/50 bDW SC PRE2

#### Complectation

Body	1
LED module	3
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements:

Net weight:

Light output\*:

PRA:

Colorful temperature\*:

Triple	
Body:	Gypsum
Illuminant:	LED
Electrical safety class:	II
Degree of protection:	IP20
Rated power:	31.3 w
Luminaire luminous flux*:	2904 lm

Color rendering index\*: Ra >80 Color temperature stability\*: MAC 3 cos \*: 0.95

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $^{**}-$  the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com