
Trimless recessed luminaire


Scult

MAC 3


Tetro S05 44W 927 DA









EHI 220-240 V



Ra >90

IP20





420x137x50 mm

Complectation

Body	1
LED module	4
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Measurements:

Net weight:	1.93 kg
3	3
Quadruple	
Body:	Gypsum
Illuminant:	LED
marmane.	
Electrical safety class:	II
Degree of protection:	IP20
Rated power:	41.5 w
Luminaire luminous flux*:	3070 lm
Light output*:	74.00 lm/w
Colorful temperature*:	2700 K
Color rendering index*:	Ra >90
Color temperature stability*:	MAC 3
COS *:	0.97
PRA·	LCA 45W 500-1400mA one4all SC

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com

PRA: