
## Large-size trimless recessed luminaire





# Simple MAX R50 D300 45W 927


ze11009013














#### Complectation

| Body               | 1  |
|--------------------|----|
| LED module         | 1  |
| Conrol gear        | 1  |
| Fastener           | 8  |
| Screw x6           | 16 |
| Screw self-tapping | 16 |
| Washer D5          | 20 |
| Suction Cup        | 2  |
| Bracket            | 4  |
| Screw M5x8         | 4  |

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

| Measurements:<br>Net weight:  | 390x390x100 mm<br>6.91 kg      |
|-------------------------------|--------------------------------|
| Round<br>Body:<br>Illuminant: | Gypsum<br>LED                  |
| mummant:                      | LED                            |
| Electrical safety class:      | II                             |
| Degree of protection:         | IP20                           |
| Rated power:                  | 44.5 w                         |
| Luminaire luminous flux*:     | 3580 lm                        |
| Light output*:                | 80 lm/w                        |
| Colorful temperature*:        | 2700 K                         |
| Color rendering index*:       | Ra >90                         |
| Color temperature stability*: | MAC 3                          |
| cos *:                        | 0.95                           |
| PRA:                          | LC 45W 500-1400mA flexC SR EXC |

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $^{**}-$  the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com