

# Large-size trimless recessed luminaire


## Simple MAX R50 D300 45W 930


ze11009014


220-240 V IP20 Ra >90 MAC 3






## Complectation

| | |
|---|---|
| Body | 1 |
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 8 |
| Screw x6 | 16 |
| Screw self-tapping | 16 |
| Washer D5 | 20 |
| Suction Cup | 2 |
| Bracket | 4 |
| Screw M5x8 | 4 |

*Dimming by TRIAC accessible on request*

## Specifications

| | |
|---|---|
| Measurements: | 390x390x100 mm |
| Net weight: | 6.91 kg |
| Round | |
| Body: | Gypsum |
| Illuminant: | LED |
| Electrical safety class: | II |
| Degree of protection: | IP20 |
| Rated power: | 44.5 w |
| Luminaire luminous flux*: | 3893 lm |
| Light output*: | 87 lm/w |
| Colorful temperature*: | 3000 K |
| Color rendering index*: | Ra >90 |
| Color temperature stability*: | MAC 3 |
| cos *: | 0.95 |
| PRA: | LC 45W 500-1400mA flexC SR EXC |

*All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.*

© Zenit STP