
## Large-size trimless recessed luminaire




MAC 3

# Simple MAX R50 D300 45W 940 DA









220-240 V


IP20

EHE



Ra >90





#### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	8
Screw x6	16
Screw self-tapping	16
Washer D5	20
Suction Cup	2
Bracket	4
Screw M5x8	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements: Net weight:	390x390x100 mm 6.91 kg
Round Body: Illuminant:	Gypsum LED
Electrical safety class: Degree of protection: Rated power: Luminaire luminous flux*: Light output*: Colorful temperature*: Color rendering index*: Color temperature stability*: cos *: PRA:	II IP20 44.5 w 4203 lm 94 lm/w 4000 K Ra >90 MAC 3 0.96 LCA 45W 500-1400mA one4all SR PRE

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $^{**}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com