# Large-size trimless recessed luminaire





MAC 3

490

Ra >80

Simple MAX R50 D400 64W 830 DA ze11009056





60°

IP20

# 495

## Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	8
Screw x6	16
Screw self-tapping	16
Washer D5	20
Suction Cup	2
Bracket	4
Screw M5x8	4

### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

30°

40

30

60°

EHE

220-240 V

Measurements:	490x490x110 mm
Net weight:	9.17 kg
Round Body: Illuminant:	Gypsum LED
Electrical safety class:	II
Degree of protection:	IP20
Rated power:	63.7 w
Luminaire luminous flux*:	6862 Im
Light output*:	108 Im/w
Colorful temperature*:	3000 K
Color rendering index*:	Ra >80
Color temperature stability*:	MAC 3
cos *:	0.97
PRA:	LCA 60W 900-1750mA one4all SR PRE

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $^{\ast\ast}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.