
## Large-size trimless recessed luminaire




MAC 3

# Simple MAX R50 D550 78W 930 DA









220-240 V


EHE



Ra >90

IP20





### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	12
Screw x6	24
Screw self-tapping	24
Washer D5	28
Suction Cup	2
Bracket	4
Screw M5x8	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements: Net weight:	640x640x110 mm 13.69 kg
Round Body: Illuminant:	Gypsum LED
Electrical safety class:	II
Degree of protection:	IP20
Rated power:	77.3 w
Luminaire luminous flux*:	7618 lm
Light output*:	99 lm/w
Colorful temperature*:	3000 K
Color rendering index*:	Ra >90
Color temperature stability*:	MAC 3
cos *:	0.95
PRA:	LCA 100W 1100-2100mA one4all SR PRE

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com