# Suspension luminaire

## Liny R RAL L500 8W 930 ze34001434



#### EHC 220-240 V IP20 Ra >90 MAC 3 Ø 68 500 Ø 78 90° 90° 2000 200 60° ,60° 400

### Complectation

Body	1
LED module	1
Conrol gear	1
Ceiling attachment	1
Suspension cord	1
Cable	1

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

#### **Specifications**

′30°

30

Measurements:	D78x500; D78x65 mm
Net weight:	1.65 kg
Tube round Body: Illuminant:	Gypsum LED
Electrical safety class:	l
Degree of protection:	IP20
Rated power:	7.8 w
Luminaire luminous flux*:	438 lm
Light output*:	56 lm/w
Colorful temperature*:	3000 K
Color rendering index*:	Ra >90
Color temperature stability*:	MAC 3
cos *:	0.4
PRA:	Mean Well APC-8-250

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

### Tenit-