

Suspension luminaire



Liny R RAL L600 8W 830
ze34001441







220-240 V



IP20

Ra >80

MAC 3



Complectation

| | |
|--------------------|---|
| Body | 1 |
| LED module | 1 |
| Control gear | 1 |
| Ceiling attachment | 1 |
| Suspension cord | 1 |
| Cable | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| | |
|-------------------------------|---------------------|
| Measurements: | D78x600; D78x65 mm |
| Net weight: | 1.86 kg |
| Tube round | |
| Body: | Gypsum |
| Illuminant: | LED |
| Electrical safety class: | I |
| Degree of protection: | IP20 |
| Rated power: | 7.8 w |
| Luminaire luminous flux*: | 508 lm |
| Light output*: | 65 lm/w |
| Colorful temperature*: | 3000 K |
| Color rendering index*: | Ra >80 |
| Color temperature stability*: | MAC 3 |
| cos *: | 0.4 |
| PRA: | Mean Well APC-8-250 |

All parameters marked with * are calculated values.
Zenith uses tried and tested components from leading suppliers.
However, it is possible for some LED technology-related faults to occur over the life of the product.
** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.