Suspension luminaire

Liny R RAL L600 8W 830 DW ze34001446



EHC 220-240 V IP20 Ra >80 MAC 3 Ø 68 600 Ø 78 90° 90° 2000 200 60° ,60° 400 ′30° 30

Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Ceiling attachment | 1 |
| Suspension cord | 1 |
| Cable | 1 |
| | |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: Net weight: | D78x600; D78x65 mm 1.94 kg |
|------------------------------------|-------------------------------|
| Tube round Body: Illuminant: | Gypsum LED |
| Electrical safety class: | I |
| Degree of protection: | IP20 |
| Rated power: | 8.1 w |
| Luminaire luminous flux*: | 508 lm |
| Light output*: | 63 lm/w |
| Colorful temperature*: | 3000 K |
| Color rendering index*: | Ra >80 |
| Color temperature stability*: | MAC 3 |
| COS *: | 0.95 |
| PRA: | LC 10/150-400/40 bDW SC PRE2 |

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.



Tenit-