

# Suspension luminaire



Liny R RAL L700 8W 930  
ze34001454







220-240 V



IP20

Ra >90

MAC 3



## Complectation

|                    |   |
|--------------------|---|
| Body               | 1 |
| LED module         | 1 |
| Control gear       | 1 |
| Ceiling attachment | 1 |
| Suspension cord    | 1 |
| Cable              | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

## Specifications

|                               |                     |
|-------------------------------|---------------------|
| Measurements:                 | D78x700; D78x65 mm  |
| Net weight:                   | 2.08 kg             |
| Tube round                    |                     |
| Body:                         | Gypsum              |
| Illuminant:                   | LED                 |
| Electrical safety class:      | I                   |
| Degree of protection:         | IP20                |
| Rated power:                  | 7.8 w               |
| Luminaire luminous flux*:     | 438 lm              |
| Light output*:                | 56 lm/w             |
| Colorful temperature*:        | 3000 K              |
| Color rendering index*:       | Ra >90              |
| Color temperature stability*: | MAC 3               |
| cos *:                        | 0.4                 |
| PRA:                          | Mean Well APC-8-250 |

All parameters marked with \* are calculated values.  
Zenith uses tried and tested components from leading suppliers.  
However, it is possible for some LED technology-related faults to occur over the life of the product.  
\*\* — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.