Suspension luminaire

Liny R RAL L700 8W 927 DW ze34001458



EHC 220-240 V IP20 Ra >90 MAC 3 Ø 68 700 Ø 78 90° 90° 2000 200 60° ,60° 400

Complectation

Body	1
LED module	1
Conrol gear	1
Ceiling attachment	1
Suspension cord	1
Cable	1

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

′30°

30

Measurements:	D78x700; D78x65 mm
Net weight:	2.16 kg
Tube round Body: Illuminant:	Gypsum LED
Electrical safety class:	l
Degree of protection:	IP20
Rated power:	8.1 w
Luminaire luminous flux*:	403 lm
Light output*:	50.00 lm/w
Colorful temperature*:	2700 K
Color rendering index*:	Ra >90
Color temperature stability*:	MAC 3
cos *:	0.95
PRA:	LC 10/150-400/40 bDW SC PRE2

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

Tenit-