

Suspension luminaire



Liny R RAL L800 8W 940 DW
ze34001470







220-240 V



IP20

Ra >90

MAC 3



Complectation

| | |
|--------------------|---|
| Body | 1 |
| LED module | 1 |
| Control gear | 1 |
| Ceiling attachment | 1 |
| Suspension cord | 1 |
| Cable | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| | |
|-------------------------------|------------------------------|
| Measurements: | D78x800; D78x65 mm |
| Net weight: | 2.38 kg |
| Tube round | |
| Body: | Gypsum |
| Illuminant: | LED |
| Electrical safety class: | I |
| Degree of protection: | IP20 |
| Rated power: | 8.1 w |
| Luminaire luminous flux*: | 473 lm |
| Light output*: | 58.00 lm/w |
| Colorful temperature*: | 4000 K |
| Color rendering index*: | Ra >90 |
| Color temperature stability*: | MAC 3 |
| cos *: | 0.95 |
| PRA: | LC 10/150-400/40 bDW SC PRE2 |

All parameters marked with * are calculated values.
Zenith uses tried and tested components from leading suppliers.
However, it is possible for some LED technology-related faults to occur over the life of the product.
** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.