## Downlight



Atis 180 11W 930 IP44 ze11020049

| EAC | 220-240 V | IP44 | Ra >90 | MAC 3 |
|-----|-----------|------|--------|-------|
|     |           |      |        |       |

× × × × ×

## Complectation

1

## Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

## Specifications

| Round<br>Body:<br>Illuminant:<br>Electrical safety class:   |  |
|---|--|
| Electrical safety class:  | Aluminum/Plastic<br>LED  |
| Degree of protection:<br>Rated power:<br>Luminaire luminous flux*:<br>Light output*:<br>Colorful temperature*:<br>Color rendering index*:<br>Color temperature stability*:<br>cos *:<br>PRA:<br>LC 10 | II<br>IP44<br>11.1 w<br>856 lm<br>83 lm/w<br>3000 K<br>Ra >90<br>MAC 3<br>0.53<br>/250/40 fixC SC SNC2 |

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.