Trimless recessed luminaire





220-240 V IP44 Ra >90 MAC 3 113 135 137 89 250 142 90° 90° 255

60°

Complectation

| Body | 1 |
|--------------------|---|
| LED module | 2 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |
| Suction Cup | 1 |
| | |

Dimming by TRIAC accessible on request

© Zenit STP

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

30°

60°

200

3Ó0

30

| Measurements: | 232x137x70 mm |
|--|---|
| Double Body: Illuminant: | Gypsum LED |
| Electrical safety class: Degree of protection: Rated power: Luminaire luminous flux*: Light output*: Colorful temperature*: Color rendering index*: Color temperature stability*: cos *: PRA: | II IP44 21.1 w 1508 lm 73 lm/w 3000 K Ra >90 MAC 3 0.95 LCA 25W 350-1050mA one4all SC PRF |

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 ** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

