## Trimless recessed luminaire



# Twins Q R25 16W 940 ze11010095




220-240 V





IP20 Ra >90


МАС 3











#### Complectation

Body	1
LED module	2
Conrol gear	2
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1
Screw x6 Screw self-tapping Washer D5	4

#### $\ \, \hbox{Dimming by TRIAC accessible on request} \\$

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements: 300x167x70 mm

Double

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 15.6 w Luminaire luminous flux\*: 1210 lm Light output\*: 80.00 lm/w Colorful temperature\*: 4000 K Color rendering index\*: Ra >90 MAC 3 Color temperature stability\*: 0.4 cos \*: Mean Well APC-8-250 PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com