Trimless recessed luminaire



Twins Q R25 22W 927 DA ze11010198




220-240 V





IP20 Ra >90


МАС 3











Complectation

| Body | 1 |
|--------------------|---|
| LED module | 2 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |
| Suction Cup | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Measurements: 300x167x70 mm

Double

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 21.1 w Luminaire luminous flux*: 1411 lm 68.00 lm/w Light output*: Colorful temperature*: 2700 K Color rendering index*: Ra >90 MAC 3 Color temperature stability*: cos *: 0.95 LCA 25W 350-1050mA one4all SC PRA:

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product

 $\ensuremath{^{**}}$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com