

# Trimless recessed luminaire

Triple Q A25 33W 930 IP44/20  
ze11010339





220-240 V



IP44

Ra >90

MAC 3



## Complectation

|                    |   |
|--------------------|---|
| Body               | 1 |
| LED module         | 3 |
| Control gear       | 3 |
| Fastener           | 2 |
| Screw x6           | 4 |
| Screw self-tapping | 2 |
| Washer D5          | 4 |
| Suction Cup        | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

## Specifications

Measurements: 363x137x70 mm

|             |        |
|-------------|--------|
| Triple      |        |
| Body:       | Gypsum |
| Illuminant: | LED    |

|                               |                      |
|-------------------------------|----------------------|
| Electrical safety class:      | II                   |
| Degree of protection:         | IP44                 |
| Rated power:                  | 33.6 W               |
| Luminaire luminous flux*:     | 2262 lm              |
| Light output*:                | 69 lm/W              |
| Colorful temperature*:        | 3000 K               |
| Color rendering index*:       | Ra >90               |
| Color temperature stability*: | MAC 3                |
| cos *:                        | 0.5                  |
| PRA:                          | Mean Well APC-12-350 |

All parameters marked with \* are calculated values.  
Zenith uses tried and tested components from leading suppliers.  
However, it is possible for some LED technology-related faults to occur over the life of the product.

\*\* — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.