Trimless recessed luminaire



Triple Q A25 33W 927 IP44/20 DA ze11010353




220-240 V





IP44 Ra >90


MAC 3











Complectation

| Body | 1 |
|--------------------|---|
| LED module | 3 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |
| Suction Cup | 1 |

$\ \, \hbox{Dimming by TRIAC accessible on request} \\$

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Measurements: 363x137x70 mm

Triple

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 31.3 w Luminaire luminous flux*: 2080 lm 69.00 lm/w Light output*: Colorful temperature*: 2700 K Color rendering index*: Ra >90 Color temperature stability*: MAC 3 cos *: 0.96 LCA 45W 500-1400mA one4all SC PRA:

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 ** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com