
## Trimless recessed luminaire


## Senit

MAC 3

# Triple Q A25 33W 940 DW









220-240 V


IP20

EHE



Ra >90





#### Complectation

| Body               | 1 |
|--------------------|---|
| LED module         | 3 |
| Conrol gear        | 1 |
| Fastener           | 2 |
| Screw x6           | 4 |
| Screw self-tapping | 2 |
| Washer D5          | 4 |
| Suction Cup        | 1 |

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

| Measurements: | 363X137X70 mm |
|---------------|---------------|
|               |               |
|               |               |

Triple

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 31.3 w Luminaire luminous flux\*: 2442 lm 81 lm/w Light output\*: Colorful temperature\*: 4000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.96 LC 45/500-1400/50 bDW SC PRE2 PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

\*\* — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com