## Trimless recessed luminaire



# Triple Q A25 24W 840 IP44/20 DW ze11010267




220-240 V





IP44 Ra >80


MAC 3











### Complectation

Body	1
LED module	3
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1

#### $\ \, \hbox{Dimming by TRIAC accessible on request} \\$

The manufacturer reserves the right to change the configuration of the LED luminaire.

## **Specifications**

Measurements: 363x137x70 mm

Triple

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 22 w Luminaire luminous flux\*: 2064 lm 97.00 lm/w Light output\*: Colorful temperature\*: 4000 K Color rendering index\*: Ra >80 Color temperature stability\*: MAC 3 cos \*: 0.95 LC 25/350-1050/50 bDW SC PRE2 PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com