## Trimless recessed luminaire



# Triple Q A25 33W 927 IP44/20 DW ze11010358




220-240 V





IP44 Ra >90


MAC 3











### Complectation

| Body               | 1 |
|--------------------|---|
| LED module         | 3 |
| Conrol gear        | 1 |
| Fastener           | 2 |
| Screw x6           | 4 |
| Screw self-tapping | 2 |
| Washer D5          | 4 |
| Suction Cup        | 1 |

#### $\ \, \hbox{Dimming by TRIAC accessible on request} \\$

The manufacturer reserves the right to change the configuration of the LED luminaire.

## **Specifications**

Measurements: 363x137x70 mm

Triple

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 31.3 w Luminaire luminous flux\*: 2080 lm 69.00 lm/w Light output\*: Colorful temperature\*: 2700 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.96 LC 45/500-1400/50 bDW SC PRE2 PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com