

# Trimless recessed luminaire

Tetro Q A25 32W 830 IP44/20 DW  
ze11010446



220-240 V



IP44

Ra >80

MAC 3



## Complectation

|                    |   |
|--------------------|---|
| Body               | 1 |
| LED module         | 4 |
| Control gear       | 1 |
| Fastener           | 2 |
| Screw x6           | 4 |
| Screw self-tapping | 2 |
| Washer D5          | 4 |
| Suction Cup        | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

## Specifications

Measurements: 475x137x70 mm

|             |        |
|-------------|--------|
| Quadruple   |        |
| Body:       | Gypsum |
| Illuminant: | LED    |

|                               |                                   |
|-------------------------------|-----------------------------------|
| Electrical safety class:      | II                                |
| Degree of protection:         | IP44                              |
| Rated power:                  | 29.1 W                            |
| Luminaire luminous flux*:     | 2556 lm                           |
| Light output*:                | 90 lm/W                           |
| Colorful temperature*:        | 3000 K                            |
| Color rendering index*:       | Ra >80                            |
| Color temperature stability*: | MAC 3                             |
| cos *:                        | 0.95                              |
| PRA:                          | LCA 45W 500-1400mA one4all SC PRE |

All parameters marked with \* are calculated values.  
Zenith uses tried and tested components from leading suppliers.  
However, it is possible for some LED technology-related faults to occur over the life of the product.

\*\* — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.