Downlight

Atis Minimal Black 146 8W 940 DW Ζ

| ze11020300 | | | EAC | 220-240 V | | IP20 | Ra >90 | MAC 3 | |
|---|---|---|--|-----------------|--------------------|------|---|-------|---------------------|
| × | × | × | | | | | | | |
| | × | × | | | | | | | |
| Complectation | | | | Specifications | | | | | |
| Luminaire | | | 1 | Measu Net we | rements: eight: | | | D1 | 46x90 mm 0,30 kg |
| The manufacturer reserves the right to change the configuration of the LED luminaire. | | | Round Body: Illuminant: | | | | Aluminum LED | | |
| | | | Electrical safety class: Degree of protection: Rated power: Luminaire luminous flux*: Light output*: | | | | ll IP20 8.7 w 447 lm * lm/w | | |

Colorful temperature*:

Color rendering index*:

cos *:

PRA:

Color temperature stability*:

4000 K

Ra >90

MAC 3

LC 10/150-400/40 bDW SC PRE2

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

0.92