Downlight



Atis Minimal Al 146 11W 840 DA ze11020432

| EHC | 220-240 V | | IP20 | Ra >80 | MAC 3 |
|-----|-----------|--|------|--------|-------|
|-----|-----------|--|------|--------|-------|

× × × × ×

Complectation

| Luminaire | |
|-----------|--|
|-----------|--|

1

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: Net weight: | D146x90 mm 0,30 kg |
|-------------------------------|-------------------------------|
| Round Body: Illuminant: | Aluminum LED |
| Electrical safety class: | П |
| Degree of protection: | IP20 |
| Rated power: | 11.4 w |
| Luminaire luminous flux*: | 1070 lm |
| Light output*: | 101 lm/w |
| Colorful temperature*: | 4000 K |
| Color rendering index*: | Ra >80 |
| Color temperature stability*: | MAC 3 |
| COS *: | 0.77 |
| PRA: | LC 25/350-1050/50 bDW SC PRE2 |

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.